

80K Coiled Tubing Unit

SBS Energy 80k Coiled Tubing Units are designed and custom built to perform live and dead well interventions on both land & offshore.

ADVANTAGES:

- UTILIZED OFFSHORE & ONSHORE
- EXPERIENCED WELL CONTROL PERSONNEL
- SMALL FOOTPRINT
- EFFICIENT MOBILIZATION/DEMOBILIZATION
- EFFICIENT TRIP SPEED
- ABILITY TO PUMP CONTINUOUSLY

SERVICES:

- MILLING
- DRILLING
- WELLBORE CLEAN OUTS
- CEMENTING
- TUBE LOGGING & PERFORATING
- AND MUCH MORE

HSE:

Our equipment meets or exceeds the safety standards of government agencies around the world. Participation of all personnel is required in safety drills, meetings and rig inspections, with documented follow up by management. All equipment and processes are designed and maintained with safety in mind. Our behavior based safety program is CHAMPS:

**Communicating
Hazards
And
Motivating
Personal
Safety**





SBS COILED TUBING SERVICES

COILED TUBING APPLICATIONS

- Well control
- Live well fishing jobs
- Tubing clean-outs (barium/asphaltene/paraffin/sand) removal
- Live well completions
- High pressure pumping
- Damaged / leaking completion repair
- Live well pressure milling
- Packer & plug fishing
- Installation of plugs, packers and liners
- Under-balanced drilling
- Perforating
- Well killing

WORKOVER APPLICATIONS

- Completions/Re-completions
- Casing cutting
- Plug & abandonment
- Wash jobs
- Straddle packers
- Zone isolation
- Pumping services
- Spotting cement
- Pipe recovery
- Squeeze jobs

80K Coiled Tubing Unit Specifications

Unit Type	HYDRA RIG
Max Pull Capacity	80,000 lbs.
Max Push Capacity	40,000 lbs.
Pipe Range	1 to 2" OD
Pipe Length	16,000' to 22,000'
Pipe Type and Grade	Quality Tubing QT-900
Blowout Preventers	Texas Oil Tools
Blowout Preventer Size	4-1/16" 10m or 15m
Injector Heads	HYDRA RIG 680
Rated Working Pressure	10,000 PSI and 15,000 PSI
Data Acquisition System	Cerberus and Orion
Fluid Pump Type	Triplex SPM HD 600
Fluid Pump Horsepower	600 HP CAT Engine
Fluid Pump Transmission	800 HP Rated
Fluid Pump Stroke Length	6"
Fluid Pump Gear Ratio	4.610:1
Fluid Pump Plunger Size	2.5" to 4.5"
Heaviest Lift on Wellhead	Injector Head 15,000 lbs.

SBS has produced this for general information only, and it is not intended for design purposes. Although every effort has been made to maintain the accuracy and reliability of its contents, SBS in no way assumes responsibility for liability for any loss, damage or injury resulting from the use of information and data herein. All applications for the material described are at the user's risk and are the user's responsibility.